




KPA EtherCAT PCI Board allows working with a PC as with an EtherCAT slave.

1 System requirements

- x86-compatible PC with a free 2.1 specs compliant PCI slot

2 Layout

- Connection of the slave in the network is carried out via In and Out connectors.
- Rotary switches (AddrH and AddrL) are used to set fixed address for the slave instead of auto-incremented by the master.
- Mode LED indicates that the slave is on and operating properly



3 Technical data

Unit	PCI board
PC interrupt	Controlled by operating system
Physical interface	Ethernet
Connector type	RJ-45 x 2
Transfer rate	100 Mbit/s
PC interface	PCI specification V2.1 compliant
Power supply	+5V (+5%); typ. 700mA
Ambient conditions	<ul style="list-style-type: none"> • Operating temperature: 0°C to 70°C • Storage temperature: -20°C to 80°C • - Humidity < 90% (non-condensing)
EtherCAT specifications	<ul style="list-style-type: none"> • 256 Kbit EEPROM • 8 Kbyte I/O process data exchange • CoE (CANopen over EtherCAT) and EoE (Ethernet over EtherCAT) • 64 Bit Distributed clocks

4 Standards



This device meets the requirements of the EC directive 89/336/EWG Electromagnetic Compatibility".

Noise emission: EN55011:1998 (CISPR 11:1997)

Noise immunity: EN61000-4-2:1995, EN61000-4-3:2002 (EN61000-4-3:1997)

EN61000-4-4:2004 (EN61000-4-4:1995)

EN61000-4-5:1995, EN61000-4-6:1996



Compliant with European Directive 2002/95/EC on the Restriction of Hazardous Substances (RoHS).

HongKe



广州虹科电子科技有限公司

工业以太网和现场总线解决方案

广州科学城科汇金谷三街2-701室



请关注



北京 010-5781 5040 | 上海 021-6728 3703 | 西安 029-8187 3816 | 广州 400-999-3848
028-6138 2617 024-8376 9335 0755-22677441 027-8193 9100